aeroqual

AQS 1 Specification Sheet

Near reference real-time monitor for particulates plus $O_3/NO_2/CO/SO_2/H_2S/CH_4/VOC$

Designed for environmental professionals who need to monitor and manage specific outdoor dust, particulates, and gases continuously, in real-time.

The AQS 1 delivers affordable and defensible measurement of PM_1 , $PM_{2.5}$, PM_4 , PM_{10} , TSP, and up to three gases, O_3 , NO_2 , CO, SO_2 , H_2S , CH_4 and VOC, all simultaneously.

The AQS 1 PM₁₀ is MCerts certified and South Coast AQMD Rule 1466 pre-approved.



Benefits

- Minimize downtime and failure with a purpose-built outdoor monitor
- Reduce site visits with filter change notifications, and two-way communications that allow you to calibrate, remotely troubleshoot, upgrade software, and change settings
- Eliminate flow checks with integrated flow sensing and automated control (PCX)
- Avoid invalid data caused by incorrect wind sensor orientation with the self-orienting met sensor
- Act swiftly before an exceedance occurs with realtime alerts
- Industry-leading gas sensing technology from Aeroqual comes fully integrated in the same compact format

What can it measure?

Specific dust fractions, gases, wind, weather, noise, and location



Who is it for?

- Industrial site operators who need to manage dust and gas emissions from site activities, within regulatory or permitted limits:
 - Construction and remediation
 - Oil and gas facilities
 - Quarry and mine operators
 - Port and bulk handling terminals
 - Landfills and Wastewater treatment plants
- Environmental consultants who want defensible data without the usual time and hassle of air monitoring projects
- Regulatory authorities who need to fill the gaps in the regulatory air quality monitoring network
- EHS managers who need to demonstrate that they are providing a safe environment for the people in their care
- Researchers who want to collect accurate, scientifically robust data without the cost of a reference monitor

Specifications | AQS 1

Particle module	Particle Sizes		Range		Display Resolution	LDL (2σ)	Precis	ion Accurac		ý	Zero Stability		Particle Size Range		
PCX1	PM ₁ , PM _{2.5} , PM 4 , PM ₁₀ <u>and</u> TSP		0 to 30,000 μg/m ³		0.1 µg/m ³	0.1 µg/m³	± 3% readi	of < 5% of ng reading		1	± 0.1 µg/m³ over 24 hour period		0.1 µm to 40 µm		
Nephelometer	PM ₁ , PM _{2.5} , PM ₁₀ <u>or</u> TSP		0 to 60,000 µg/m ³		0.1 µg/m³	<1 µg/m³	± 1% readi	of ±(2 µg/m³ + ng of reading		5% :)	± 0.1 µg 24 hou	/m³ over r period	0.1 µm to 40 µm		
Gas module	e Range		Display Resolution		Noise ero; Span of reading	Lower Detection Limit (2ơ)		Precision		Linearity (% of FS)		Drift 24 hour Zero; Span % of FS			
Ozone O ₃	₃ 0-500 ppb		0.1 ppb		<1 ppb; 1%	<1 ppb		2%	2% of reading or 2 ppb		%	1 ppb; 0.2%			
Nitrogen dioxide NO ₂	e 0-500 ppb		0.1 ppb		<1 ppb; 1%	<1 ppł	2% of or 2		of reading or 2 ppb	1.5	5%		1 ppb; 0.2%		
Carbon Monoxide CO	0-25 D ppm		0.001 ppm	().02 ppm; 1%	0.04 ppm		3% of reading or 0.05 ppm		1'	%	0.14 ppm; 2%			
VOC (Low range)	0-500 ppb		0.1 ppb		<1 ppb; 1%	<1 ppł	<1 ppb 2% of reader 2% of the reader 2%		of reading or 1 ppb	1'	%	1 ppb; 1%			
VOC (High range)	0-30 ppm		0.01 ppm		<0.1 ppm; 1%	<0.1 pp	n 2% of readi or 0.05 pp		of reading 0.05 ppm	2	!%	0.1 ppm; 1%			
Hydrogen Sulfide H₂S	0-5,000 ppb		0.1 ppb		1 ppb; 0.1%	2 ppb	ppb 1% of r 3		f reading or 3 ppb	0.	0.5%		<1 ppb; <0.5%		
Sulfur Dioxide SO ₂	0-10, pr	,000 ob	0.1 ppb		1 ppb; 0.02%	2 ppb)	0.149	% of reading or 2 ppb	0.6	6%	1 ppb; 0.3%			
Methane CH₄	0-5 pp	00 m	0.01 ppm	(0.02 ppm; 0.3%	0.04 pp	om	0.4% or	% of reading r 0.06 ppm		1%	0.04ppm; 1%			
					Base Syste	em Specifica	ations								
Control system Em			Embedded PC with on board data storage (>5 years)												
Communication	Standard: WIFI, Ethernet (LAN) Optional modem: Cellular IP 4G LTE, Integrated high gain antenna														
Software		Talk to our sales team to learn more about Aeroqual's software products.													
Averaging period		User selectable averaging interval from 1 min to 24 hr													
Power requirements ³		100-260 VAC or 9-36VDC battery/solar: Power usage: 15 to 30 W max steady state (configuration dependent)													
Enclosure		Lockable IP65 GRP cabinet with integrated aluminum solar shield armor, built in temp/RH sensor (PCX)													
Dimensions		685 mm x 330 mm x 187 mm (27" x 13" x 7%") Includes PM inlet													
Weight⁴		< 13 kg (28.6 lbs)													
Operating range		-10 °C to +45 °C (14 °F to 113 °F) Low temperature operation extendable with winterization pack													
Mounting		Pole, tripod and wall mounting brackets included													
Factory integrated sensors ⁵		Gill WindSonic (ultrasonic wind sensor), Vaisala WXT536 (weather transmitter), Cirrus MK427 Class 1 (noise sensor), Novalynx Pyranometer (solar radiation), Airmar 200WX (weather station)													
Compatible tested sensors		A wide (sound	range of other s level meter) and	ensors (Svante	can be connecte k SV971A (sounc	d including: \ l level meter).	/ictron S Contact	martS Aero	Solar MMPT 10 qual for more	0-20 (inform	(solar cl nation.	narge con	troller), BSWA 308		
Inputs/Outputs ⁶ 0-5V analog input, 4-20mA input, configurable relay output															
					PM Syste	m Specifica	tions								
Inlet Omni-directional sample inlet with integrated heater															
Pump	Long lif	e 12 V brushless	DC dia	phragm, with au	tomated flow	measure	ement	and control s	system	(PCX)					
Optics	PCX: 65	50 nm industrial	laser, h	emispherical-foo	cusing OPC, N	ephelor	neter:	670 nm laser,	near-f	forward	scattering	g nephelometer			
Zero calibration Auto-zero on start-up and at user selected intervals															
Gas System Specifications															
Inlet Inert glass-coated stainle					ss steel and Teflon sample inlet										
Pump		Long lif	Long life 12 V brushless DC diaphragm												
Module Tech		Automa	atic Baseline Cor	rection	tion (ABC) minimizes sensor baseline drift										
Compliance															
In conformity with	n EC Dire	ectives 20	14/30/EU and 20	14/35/1	EU; FCC 47 CFR I	Part 15; RoHS	3 (EU201	15/863	B), REACH						
Certified Modules				M	MCERTS					South Coast AQMD rule 1466					
				Ye	Yes - Sira MC210385/00				Yes	Yes					
				PN PN	1 ₁₀ 1 _{2.5}				Yes N/A	res N/A					

¹Representative values for PM_{2,5}; for individual channel performance please see the Aeroqual Technical Performance Guide
²4G LTE not available in all markets
^{3.4} Configuration used for power and weight calculations: base unit, nephelometer, PM₁₀ sharp cut, modem, heater on
⁵ Optional

- ⁶ Available with optional PDI Core upgrade



